


1200 - 1240mm Black Inline Sliding Shower Screen

SPACINGS BASED ON THESE ASSUMPTIONS:

1. Fixed panel installed with Purty wall brackets which produces a 3mm silicone joint gap. If wall channel is used, specified opening sizes overlap; etc will change.
2. Edge of glass door must remain 10mm from wall. 10mm door bulbs recommended to use for buffering or if not used, 10mm safety margin gap required.
3. When door is open, minimum 15mm gap is required from wall for safety margin buffering.

*When using a 650mm wide fixed panel, it is important to purchase 1x slimline wall bracket separately (STAL-RWBS-/STAL-RWBS-ORO/STAL-RWBS-NIKL) due to space restrictions between the rail fixing bracket and the wall.



Kit includes

-
- 1 / 2

1200 - 1240mm Black Inline Sliding Shower Screen

[Click Here to View or Sliding Shower Screen Full Brochure](#)

[Click Here to View or Sliding Shower Screen Installation Guide](#)

Rating: Not Rated Yet

Price

\$832.00

\$832.00

[Ask a question about this product](#)

Description

Suits Wall to Wall Opening of: 1200mm to 1240mm

Kit includes

- 1 x 600mm x 2038mm Door Panel
- 1 x 650mm x 2050mm Fixed Panel
- 1 x Matt Black Sliding Door Kit
- 2 x Matt Black Wall Brackets
- 1 x Door Bump Stop
- 1 x Matt Black 1650mm Long Pre-Drilled Rail
- 1 x Matt Black Slimline Rail Wall Bracket
- 1 x 20 Pack of 1.5mm Clear Setting Blocks
- 1 x Bostik 6s Silicon
- 1 x Ultraloc Threadlocker 3242 Compound

[Click Here to View or Sliding Shower Screen Full Brochure](#)

[Click Here to View or Sliding Shower Screen Installation Guide](#)